ULTRA-QUIET BLOWERS

Stealth II Blower



FEATURES

- · High performance motor runs cooler & quieter
- High impact resistant construction
- Has been tested, certified and listed by UL to requirements of both UL & CSA standards

Stealth Air Blowers									
Part No.	Description	HP	Volts	Amps					
700-3011-000	1 ½" S / 2" Spigot	1.0	110	6.7					
700-3151-000	1 1/2" S / 2" Spigot	1.5	110	7.6					
700-3102-000	1 ½" S / 2" Spigot	1.0	220	4.0					
700-3152-000	1 ½" S / 2" Spigot	1.5	220	4.2					
700-3201-000	1 1/2" S / 2" Spigot	2.0	110	8.8					
700-3202-000	1 1/2" S / 2" Spigot	2.0	220	5.8					

Santanna II

FEATURES

- . Side or bottom mount
- Heat-free due to open air system that eliminates back pressure build-up
- Internal check valve resists water damage
- . Mounting body is Hi-Temp material
- Side/Bottom outlet is perfect for any outdoor installation; slip plug is included for the outlet not in use
- · Protected for the locked motor condition
- Has been tested, certified and listed by UL to requirements of both UL and CSA standards
- Santanna II Air Blowers for residential use are backed by a full one-year, no water damage, warranty
- · Bracket on case for easy mounting
- . High impact strength construction
- Indoor/outdoor use

Air Check Valves

Santannal

600-8140 (included) & 600-8160 (U.L. Listed SA8537)

1½" Slip, 2" Spigot x 1½" S - 2" Spigot, ¼ lb. Spring

Number Blower of Jets Size 4 - 7 1 HP 8 - 13 1½ HP

14 + 2 HP

When using a blower to turbo charge jets, care must be taken in sizing and installation. It is important not to oversize the blower.

Santanna Air Blowers										
Part No.	HP	Volts	Amps	Orifice Dia.	Air Flow (CFM)	PSI				
750-3101-280	1.0	110	7.0	2"	115	2.1				
750-3102-280	1.0	220	3.5	2"	113	3.8				
750-3151-280	1.5	110	8.0	2"	120	4.2				
750-3152-280	1.5	220	4.0	2"	108	2.1				
750-3201-280	2.0	110	9.0	2"	128	3.8				

6.0















750-3202-280

2.0 220

119

42