



WINTER COVER LIMITED WARRANTY

WARNING
AVOID DROPPING FEEL - THIS IS NOT A SAFETY COVER
 This tarp cover will not protect vehicles, boats, machinery, etc. from damage. Limited to tarp cover
 cover, zipper, flysheet, mesh - does not include tie out or stakes. Repairs (tarp cover) require return
 cover or vehicle - replacement tarp cover requires an additional service charge of \$100.00.

COVER: 3 YEAR LIMITED WARRANTY (3 YEARS FULL)
DESIGN: LIFE OF COVER.

NOTE: Before installing your new winter cover, please be sure to check thoroughly to insure that the tie out, stakes and fasteners (NOT INCLUDED) covers are not subject for exchange or covering against defects or incorrect use.

Midwest Canvas Corp. ("Manufacturer") warrants to the original consumer purchaser of a Midwest Canvas Winter Tarp Cover when used under normal use in accordance with the manufacturer's winter cover installation instructions, that the manufacturer of its nylon webbing, tie or change (fasteners or Weight Changes), or replace any cover where the fabric deteriorates (i.e., Loss of 50% of total break strength), in accordance with the following product replacement schedule.

First Year and Second Year (conditions as follows) (Replacement Rate)
 Year: Year 1: 50% of current retail suggested list price.
 Year: Year 2: 25% of current retail suggested list price.
Fourth Year
 Year: 10% of current retail suggested list price.
Sixth Year
 Year: 5% of current retail suggested list price.
Eighth Year
 Year: 5% of current retail suggested list price.
Tenth Year
 Year: 5% of current retail suggested list price.

Additional to the above life of the cover, the manufacturer offers to repair the winter cover to be defective (i.e., unless the stitching has come apart or there is no repair to a seam), at its option to the original consumer purchaser (fasteners or Weight Changes).

NOTE: Excessive abrasion, holes caused from wear, wind damage, and punctures (including nail) are specifically excluded from the warranty in areas of high wind, the anchoring of the cover is important. The anchoring should prevent any lifting of the cover.

ALL IMPLIED WARRANTIES, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED TO THE BRIGHT 90 DAY PERIOD AFTER THE DATE SOLD TO THE ORIGINAL PURCHASER AND THEREAFTER ARE EXCLUDED. However, some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to the purchaser.

Manufacturer will not be liable for any incidental or consequential damages resulting from any defects in design, workmanship or material. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation may not apply to the purchaser.

The warranty gives the original consumer purchaser specific legal rights, and purchaser may also have other rights which may vary from state to state. All warranty claims should be handled directly with Midwest Canvas Corp. Do not take your cover back to where it was purchased. Please see them at:

LIMITED WARRANTY REGISTRATION CERTIFICATE

THIS CARD MUST BE MAILED WITHIN 10 DAYS OF YOUR PURCHASE

WARNING AVOID DROPPING FEEL - THIS IS NOT A SAFETY COVER
 This tarp cover will not protect vehicles, boats, machinery, etc. from damage. Limited to tarp cover
 cover, zipper, flysheet, mesh - does not include tie out or stakes. Repairs (tarp cover) require return
 cover or vehicle - replacement tarp cover requires an additional service charge of \$100.00.

Cover Model _____ Date Purchased _____

Dealer _____ Retail Price Paid _____

The following information may be answered at your option

Part Model and Size _____ Date Purchased _____

Is this your first Midwest Canvas Cover? Yes No

Cover was purchased for use of

- | | |
|--|---|
| <input type="checkbox"/> Suggestion of Dealer or Retailer | <input type="checkbox"/> Advertising |
| <input type="checkbox"/> Suggestion of Retail Manufacturer | <input type="checkbox"/> Tourism destination |
| to cover used year round? | <input type="checkbox"/> Yes <input type="checkbox"/> No |
| Cover was purchased for? | <input type="checkbox"/> Winter use <input type="checkbox"/> Cleanliness <input type="checkbox"/> Retention of Heat <input type="checkbox"/> Retention of Chemicals |



MIDWEST CANVAS CORP. • 4611 West Lane Street • Chicago, Illinois 60644

WINTER COVER INSTALLATION INSTRUCTIONS

General Procedures

1. Since the cover is designed to rest on the pool's wall, it is important to be sure your pool is not leaning prior to installation.
2. Your covering must be unwound along and around exposed surfaces. However it is required that your cover be protected from sharp corners, rough edges, or any hard surfaces that may cause abrasion. Packing such as old towels, foam blankets or other similar materials are recommended.
3. It is important that covers be installed properly and snugly so that the wind will not cause damage to the cover by getting under the cover and causing it to blow or flap.

In-Ground Pool Installation

1. Be sure that the cover will be supported by the water in the pool and that the cover is not in direct contact with any sharp rough or abrasive surfaces.
2. Lower the water level in your pool below the skimmer (the more than 18 inches below the skimmer).
3. Place the cover on the ground and spread evenly over the pool.
4. Insert inflated water bags into the skimmer holes (the covers without holes by the water bags directly on to the outside perimeter of the cover).
5. The water bags must cover the entire perimeter of the cover to prevent wind from getting under the cover and causing the cover to blow or flap. Caution such blowing or flapping in the wind can cause serious damage to your cover. Therefore, be sure the waterbags are placed end-to-end as in Figure 1.
6. Fill the water bags. If you are in an area of extreme cold, fill the water bags only to 1/2 full to allow for ice expansion.



Fig. 2



Fig. 1

Above-Ground Pool Installation

1. Be sure that the cover will be supported by the water in the pool and that the cover is not in direct contact with any sharp rough or abrasive surfaces.
2. Lay out the cover on the ground. Thread the cable through the grommets (or loops). The cable must remain on the outside of the cover, except between the pairs of grommets (Figure 3).
3. For covers with a turnbuckle end clamp, open the turnbuckle until only the ends of the cover show on the inside. Put one end of the cable through the top of one turnbuckle screw and secure it with a cable clamp (See Figure 3). Put the other end of the cable through the other loop. Pull the cable tight and secure it with the second clamp.

Figure turnbuckle by using it as shown in Figure 4. Make sure the cable lies on the outside of the cover at around the pool except where it goes through the pairs of grommets. The cable must fit tight against the wall of the pool or against steel from getting underneath the cover. To tension or remove cable turn turnbuckle in the opposite direction.



Fig. 3



Fig. 4

4. For covers with a winch hoist and cable end, thread the hole of one end of the winch into the center grommet. Turn the handle a few times to secure the cable. Repeat the other cable end through the other hole in the winch and pull the cable through the handle as far as it will go. Turn the winch handle to tighten the cable. Make sure cable lies on the outside of the cover all around the pool except where it goes through the pairs of grommets. The cable must fit tightly against the end of the pool to prevent wind from getting underneath the cover. To tension or remove cable, pull from an top of winch and turn handle in the opposite direction (see Figure 5).



Fig. 5

5. Before placing cover over the pool, pour water about 1/2 inch below the 1/2" from top of pool where a trough-the-wall skimmer is used (cover w/o the skimmer opening, inflate flotation pillow (available from your dealer) and secure the pillow in center of pool) by being grommets ends with water bags in pool instead. Place the cover pillow to form a floaters against the pool wall as the water around the circumference (See Figure 6). Put one end of cover over pool wall it is important that the cover fit snugly against the wall to prevent wind from getting under the cover and causing the cover to blow and flap. Caution such blowing and flapping can cause serious damage to the cover. If you cannot get a snug fit you must back-fill openings between the cover and the pool wall.



Fig. 6

Place
Stamp
Here

MIDWEST CANVAS CORPORATION
WARRANTY DEPARTMENT
4635 W. Lake St.
Chicago, IL 60644