

Residential Models

GPC23-210 Electrical Technical Specifications: 110/115V 1-PH 60/50H 8.5 Amps						
	MODEL	POOL SIZE	SHIP WT	H X W	PIPE IN/OUT	VOLUME
	GPC23	<8 GAL	105 LBS	50" X 28"	1.5" / 1.5"	25 GPM
	GPC25	<20 GAL	125 LBS	52" X 34"	1.5" / 1.5"	30 GPM
	GPC210	<30 GAL	150 LBS	54" X 42"	1.5" / 1.5"	45 GPM

GPC-23 AND 25 MODELS REQUIRE 2 X 2 PAD GPC-210 REQUIRES 3 X 3 PAD

**Please Note: Some pools can expect less cooling if they have pebble (light or dark), quartz, tile, or dark plaster finishes due to the added heat load by these finishes from the sun. However, if your pool has a pebble finish (any color), quartz, tile, or any dark colored plaster bottom and your pool volume is close to the gallon limits above, you should go up one size when choosing your unit.*

Commercial Models

GPC215 and GPC220 Electrical Technical Specifications: 110/115V 1-PH 60/50H 8.5 Amps						
GPC230 and Larger Electrical Technical Specifications: 220/480V 3-PH 60/50H 8-12 Amps						
	MODEL	POOL SIZE	SHIP WT	H X W	PIPE IN/OUT	VOLUME
	GPC215	<45 GAL	200 LBS	60" X 46"	2" / 2"	45 GPM
	GPC220	<80 GAL	250 LBS	63" X 55"	2" / 2"	60 GPM
	GPC230	<120 GAL	300 LBS	68" X 62"	2.5" / 2.5"	80 GPM
	GPC240	<180 GAL	425 LBS	75" X 72"	2.5" / 2.5"	125 GPM
	GPC250	<225 GAL	525 LBS	75" X 80"	3" / 3"	150 GPM
	GPC260	<275 GAL	600 LBS	75" X 82"	3" / 3"	180 GPM
	GPC270	<325 GAL	700 LBS	80" X 85"	4" / 4"	200 GPM
	GPC280	<450 GAL	750 LBS	80" X 86"	4" / 4"	240 GPM
	GPC2100	<550 GAL	1000 LBS	86" X 105"	4" / 4"	300 GPM

CALL FOR COMMERCIAL MODEL PAD DIMENSIONS & SPECIFICATIONS
 ALL COMMERCIAL MODELS ARE EQUIPPED WITH THERMOSTAT CONTROLS