

EZ48® Thru-Bolt Pool & Spa Motors

5.5" Frame Diameter



FEATURES:

- Open Dripproof
- Sealed Ball Bearings
- Class B Insulated
- 1081 Design
- 50°C Ambient
- 3 O'clock Conduit
- Rigid Base
- Thermally Protected
- 3-1/2" Shaft Height
- Shaft Thread - 3/8-16 UNC-2A RH
- 303 Stainless Steel Shaft
- **Discount Symbol: DS-FPS**

Single Speed - 1.5 Compartment

HP	SF	RPM	Voltage	Freq	SF Amps	Catalog Number	List	Motor Frame	Length Less Shaft	Ship Wt. (lbs)
1/2	1.00	3450	115	60	7.5	EZBN23	\$182	48Y	8.7	15
3/4	1.00	3450	115	60	10.0	EZBN24	\$194	48Y	8.7	17
1	1.00	3450	115	60	12.0	EZBN25	\$214	48Y	9.3	22
1 1/2	1.00	3450	115	60	7.7/15.4	EZBV35	\$252	48Y	9.8	25
	1.00	3450	230/115	60	16.0	EZBN35	\$252	48Y	9.8	25

Two Speed - 1.5 Compartment

HP	SF	RPM	Voltage	Freq	SF Amps	Catalog Number	List	Motor Frame	Length Less Shaft	Ship Wt. (lbs)
3/4 / 1/10	1.00	3450/1725	115	60	9.8/3.2	EZBN36	\$252	48Y	8.7	17
1 / 1/8	1.00	3450/1725	115	60	12.2/3.8	EZBN37	\$268	48Y	9.2	22
1.5 / 0.188	1.00	3450/1725	115	60	16.0/4.8	EZBN50	\$357	48Y	11.6	25

Rocker Switch Cover Assembly available: Two Speed - LO-OFF-HI-X2975862300000L One Speed - ON-OFF-X2975862200000L

Catalog numbers are for competitive comparison purposes only.

† All marks shown within this document are properties of their respective owners.

